

CARMIX TRAILER PUMP 15

CARMIX
4x4 mixers & dumpers



ACCESSORIES ON DEMAND

STOWABLE CE KIT

CONCRETE PUMPING KIT:

- 07 Steel pipes dn 4" L 3 mt for Victaulic 4"
- 01 Rubber hose 4" L 3 mt for Victaulic 4"
- 01 Steel bends dn 4" r=250/90° Victaulic
- 02 Steel bends dn 4" r=250/45° Victaulic
- 12 Victaulic coupling dn 4"
- 15 Gasket for Victaulic coupling dn 4"
- 02 Cleaning ball dor hose diam. 150/200
- 01 Basket for cleaning ball recovery dn 4"
- 01 90° bend with ball inlet port
- 01 Bend top 100 Victaulic

SHORTCRETING SPRITZBETON KIT:

- 02 Rubber hose dn 50 mm, l 10 m Victaulic 2" - Victaulic 2"
- 01 Rubber hose dn 50 mm, l 10 m Victaulic 2" - can dm 50
- 01 Complete hopper gun dn 50 with fast Geka coupling 3/4" for air
- 01 Reduction cone dn 100 (4")-dn 50 (2") Victaulic l = 1000 m
- 01 Hanging belt for hose
- 02 Cleaning ball for hose dn. 50
- 01 Victaulic coupling dn 4"
- 02 Gasket for Victaulic coupling dn 4"
- 03 Victaulic coupling dn 2"
- 06 Gasket for Victaulic coupling dn 2"
- 01 Gasket for cam coupling dn 50

CARMIX TRAILER PUMP 15



- + **2-cylinder piston pumps, hydraulic driven**
Complete with Automatic Greasing System
- + **Max pumping Height: 60-70 m**
Max pumping distance: 80-90 m
- + **Flow rate up to 15 m³/h**
- + **Max aggregate size 25 mm**
- + **Pumping pressure 70 bar**
- + **Hopper capacity 240 liters**
 - Yanmar 31HP 3 Cylinders liquid cooled diesel engine
 - Concrete hopper with agitator
 - Grid with 12V vibrator
 - Pumping unit with S-Tilting valve for automatic compensation of clearance and wear
 - EasySprit system: best pumping performance also at low flow rate
 - 4" Victaulic delivery manifold (= 100 mm)
 - Control panel with electromechanical devices
 - 4-Function wire remote control
 - On request road-towable unit complete with parking brake and lights
 - Compact and easy to move
 - Dimensions: w/l/h: 1495/4100/1540 mm
 - Weight: 1550 kg



CARMIX
EVERYWHERE
YOU BUILD